


Euro Hexsert® 39101



For installation information please refer to the tooling overview and manuals on our website www.avdel-global.com.
 Pour les conditions de pose, merci de vous référer à la description de l'outil et aux manuels disponibles sur notre site Web.
 Angaben zur Verarbeitung entnehmen Sie bitte der Geräteübersicht und den Betriebsanleitungen auf unserer Website.
 Per informazioni sull'installazione preghiamo consultare i manuali e la panoramica degli attrezzi sul nostro sito web.
 Para ver información sobre máquinas de colocación, consulte nuestra página web, apartados visión general de máquinas y manuales.

English	Français	Deutsch	Italiano	Español
Hexagonal body	Hexagonal corps	Hexagonaler Schaft	Hexagonal corpo	Hexagonal cuerpo
Low carbon steel*	Acier bas carbone*	Stahl*	Acciaio a basso tenore di carbonio*	Acero bajo en carbono*
Zinc plated	Revêtement zingué	Verzinkt	Zincato	Zincado
Clear trivalent passivated	Passivation claire trivalente	Klar chromatiert, Cr6-frei	Passivazione chiara trivalente	Pasivado claro trivalente

* : DIN EN 10263-2 Qst 34-3, BS EN/DIN 10263-2 C8C, Werkstoff 1.0213, SAE 1008



Ø	A/F +0.1/-0	e (grip)		A ± 0.08	B max.	D ± 0.07	F ± 0.08	J max.	M ± 0.50	P max.	Part No/ref
		min.	max.								
M4 x 0.7	6.0	0.50	2.00	5.89	7.80	0.69	5.89	9.20	10.50	6.00	39101-74020
M5 x 0.8	7.0	0.50	3.00	6.89	9.10	0.77	6.89	11.20	12.70	8.60	39101-75030
M6 x 1.0	9.0	0.50	3.00	8.89	11.60	0.91	8.89	13.40	15.00	10.10	39101-76030
M8 x 1.25	11.0	0.50	3.00	10.89	14.20	1.07	10.89	16.20	17.50	11.40	39101-78030
M10 x 1.5	13.0	1.00	3.50	12.89	16.40	1.07	12.89	18.50	20.20	13.20	39101-70035

all dimensions in mm / en millimètres / alle Maße in mm / in millimetri / en milímetros

Ø	Recommended max torque	Pull-out	Torque-to-turn	Push-out
	Nm max.	kN	Nm min.	kN
M4 x 0.7	5.1	6.3	4.2	1.4
M5 x 0.8	7.9	8.8	7.5	2.6
M6 x 1.0	12.4	14.4	10.7	3.2
M8 x 1.25	32.0	15.0	22.7	4.1
M10 x 1.5	45.0	19.7	38.5	5.2



An Acument™ Global Technologies Company

www.avdel-global.com

© 2007 Acument Intellectual Properties, LLC

Hexsert® is a trademark of Avdel UK Limited

05.2008

Data shown is subject to change without prior notice as a result of continuous product development and improvement policy.
 Your local Avdel representative is at your disposal should you need to confirm latest information.